

STRAINERS AND PRESSURE REDUCING VALVES


RP25X

143

EUROBRASS PRESSURE REDUCING VALVE



SUITABLE FOR DOMESTIC WATER SERVICES, HEATING AND AIR-CONDITIONING PLANTS, COMPRESSED AIR SYSTEMS. IT CAN BE INSTALLED IN ANY POSITION: VERTICAL, HORIZONTAL, OBLIQUE.



Compensated operation
 Female/female threads
 Body in nickel-plated brass
 Minimum and maximum working temperatures: 0°C, 130°C in absence of steam.
 Maximum inlet pressure: 25 bar
 Outlet pressure can be adjusted between 0.5 and 6 bar.
 Factory preadjustment: 3 bar
 Outlet pressure gauge connections 1/4" on both sides.

SIZE	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
A (mm)	77	85	89	125	130	138	148	177	190
B (mm)	120	150	160	220	220	250	256	285	310
WORKING PRESSURE kg/cm ² bar	25	25	25	25	25	25	25	25	25
WORKING PRESSURE PSI	360	360	360	360	360	360	360	360	360


Threads:
 ISO228
 (equivalent to
 DIN259 and
 BS2779)

360

MINIBRASS PRESSURE REDUCING VALVE



SUITABLE FOR DOMESTIC WATER SERVICES, HEATING AND AIR-CONDITIONING PLANTS, COMPRESSED AIR SYSTEMS. IT CAN BE INSTALLED IN ANY POSITION: VERTICAL, HORIZONTAL, OBLIQUE.



non distribué

SIZE	3/8"	1/2"	3/4"
A (mm)	60	60	60
B (mm)	93	93	93
C (mm)	26	26	30
WORKING PRESSURE kg/cm ² bar	15	15	15
WORKING PRESSURE PSI	220	220	220

Female/female threads
 Body in nickel-plated brass
 Minimum and maximum working temperatures: 0°C, 80°C.
 Maximum inlet pressure: 15 bar
 Outlet pressure can be adjusted between 1 and 4 bar.
 Factory preadjustment: 3 bar
 Threads: ISO228
 (equivalent to DIN259 and BS2779)

4


REMIT

361

MINIBRASS PRESSURE REDUCING VALVE WITH PRESSURE GAUGE CONNECTION



SUITABLE FOR DOMESTIC WATER SERVICES, HEATING AND AIR-CONDITIONING PLANTS, COMPRESSED AIR SYSTEMS. IT CAN BE INSTALLED IN ANY POSITION: VERTICAL, HORIZONTAL, OBLIQUE.



SIZE	3/8"	1/2"	3/4"
A (mm)	60	60	60
B (mm)	110	110	110
C (mm)	26	26	31
WORKING PRESSURE kg/cm ² bar	15	15	15
WORKING PRESSURE PSI	220	220	220

Female/female threads
 Body in nickel-plated brass
 Minimum and maximum working temperatures: 0°C, 80°C.
 Maximum inlet pressure: 15 bar
 Outlet pressure can be adjusted between 1 and 4 bar.
 Factory preadjustment: 3 bar
 Outlet pressure gauge connections 1/4".
 Threads: ISO228
 (equivalent to DIN259 and BS2779)



ART. 143-360-361